



SPECIF	ICATIONS	REVV8520T3	REVV8524T3
Body:	Length	22'0"	26'0"
	Width	8'4"	8'4"
Overall:	Length	25'0"	29'0"
	Width	8'6"	8'6"
	Height	9'2"	9'2"
Interior:	Length	21'6"	25'6"
	Width	8'1"	8'1"
	Height	7'0"	7'0"
Width Between Wheel Boxes:		83"	83"
Platform Height:		18"	18"
Axle:	Quantity	Tandem	Tandem
	GVWR	9,990 lbs.	9,990 lbs.
	Suspension	Spring	Spring
	Electric Brakes	Standard	Standard
Tires:	Size	ST225/75R15	ST225/75R15
	Load Range	D	D
	Туре	Radial	Radial
Hitch:	Ball Size	2 <sup>5</sup> / <sub>16</sub> "	2 <sup>5</sup> / <sub>16</sub> "
	To Top of Ball	21"	21"
Rear Door:	Style	Ramp	Ramp
	Beavertail Length	48"	48"
	Width x Height	94" x 80"	94" x 80"
	Hardware	Bar Locks	Bar Locks
Flush Lock Side Door:		48" x 78"	48" x 78"
Tube Main Rails		2" × 6"	2" × 6"
Curb Weight		3,650 lbs	4,480 lbs
Payload Capacity		6,340 lbs	5,510 lbs.
12V Trailer Connector		7-way	7-way

## STANDARD FEATURES

- Roof and Sidewall Design
  - -16" OC Floor Crossmembers -16" OC Tube Wall Posts

  - -16" OC Roof Framing
- 12" Extended A-Frame with Center Tube
- Smooth .030 Bonded Aluminum Exterior
- Sidewall Flow-Thru Vents
- Polished Aluminum Rear Corners & Rear Header
- 24" Stoneguard
- 48" Side Entry Door with Flush Lock & Recessed Step
- Bar Lock Assembly on Side Door (Add'l Security)
- 9mm White Vinyl Sidewall Liner
- White Vinyl Ceiling Liner
- Black Coin Rubber Floor & Ramp Covering
- Straight Base Cabinet with Black Coin Countertop
- Overhead Cabinet
- 16" ArmorTech Covered Ramp Extension
- 5000 lb. D-Rings (4)
- 15" Radial Tires
- Black SpitFire Aluminum Wheels
- Slim Line LED Tail Lights (Clear Lens)
- 12v LED 14" Ceiling Lights (4)
- 120v 15a Duplex Recepts (2)
- 120v 30A Motorbase with Twist Lock Connect
- 120v 30A Power Cord/Plug 25'
- 30 Amp AC/DC Power Distribution Panel with Converter
- 3 Year Limited Warranty

## **POPULAR OPTIONS**

- Phantom Trim Package
- LED Race Light
- Frame & Wire for Roof Mount A/C



