

SILVERSPORT

BY WELLS CARGO

ALL-ALUMINUM WAGON SS

WELLS
CARGO®



Trailers shown may feature optional equipment available at an additional charge.

STANDARD FEATURES

- V-Front Bull Nose Profile
- Aluminum Smart Frame™ Technology
 - 16" OC Tube Main Rails
 - 16" OC Tube Floor Crossmembers
 - 16" OC Tube Wall Framing
 - 16" OC Tube Roof Framing
 - Dust-Proof Sidewalls
- All-Aluminum Hardware
- Adjustable Height 2-5/16" Wallace Forge® Cast Coupler
- 8,000 lb. Dropleg Sidewind Jack
- Dexter Torflex® Torsion Axles with E-Z Lube Hubs
- Goodyear® Radial Tires on Silver SpitFire Aluminum Wheels
- 3/4" PlexCore High-Performance Flooring
- 3/8" PlexCore High-Performance Sidewall Liner
- 5,000 lb. Floor D-Rings
- 12v Clear Lens LED Tail Lights
- 12v Clear Lens LED Clearance Lights
- 12v LED High Output LED Dome Lights with Switch (800 Lumens)
- Rear LED ID Bar with Built-In Loading Light with Switch
- Flow-Thru Sidewall Vents (2)
- 1-Piece Aluminum Roof
- .030 Aluminum Exterior — Bonded for Smooth Appearance
- 24" ATP Stoneguard
- ATP Fenders (7'W) or Smooth Fenderettes (8.5'W)
- Heavy-Duty 36"W Side Door with Flush Lock & Dead Bolt (1-1/2" Core)
- Rear Double Doors (Rear Ramp Door Optional)
- 6-Year Limited Warranty

SILVERSPORT

BY WELLS CARGO



ALL-ALUMINUM WAGON SS

Model		WSS714T2*	WSS716T2*	WSS8516T2*	WSS8520T2*	WSS8524T3
Body:	Length (Incl. "V")	17'0"	19'0"	19'0"	23'0"	27'0"
	Width	7'0"	7'0"	8'4"	8'4"	8'4"
Overall:	Length	19'1"	21'1"	21'1"	25'1"	29'1"
	Width	8'6"	8'6"	8'6"	8'6"	8'6"
	Height	8'4"	8'4"	8'6"	8'6"	8'6"
Interior:	Length	16'7"	18'7"	18'7"	22'7"	26'7"
	Width	6'9"	6'9"	8'1"	8'1"	8'1"
	Height	6'6"	6'6"	6'6"	6'6"	6'6"
Platform Height:		18"	18"	20"	20"	20"
Axle:	Quantity	Tandem	Tandem	Tandem	Tandem	Tandem
	Type	10° Up	10° Up	10° Up	10° Up	10° Up
	Suspension	Torflex®	Torflex®	Torflex®	Torflex®	Torflex®
	Brakes	STD	STD	STD	STD	STD
Tires:	Size	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST225/75R15
	Load Range	D	D	D	D	E
	Type	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial
Wheels:		Aluminum SpitFire	Aluminum SpitFire	Aluminum SpitFire	Aluminum SpitFire	Aluminum SpitFire
Hitch:	Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
	To Top of Ball	17" to 21"	17" to 21"	19" to 23"	19" to 23"	19" to 23"
Hitch Weight		10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%
GVWR		7,000 lb.	7,000 lb.	7,000 lb.	7,000 lb.	9,990 lb.
Curb Weight		2,090 lb.	2,360 lb.	2,740 lb.	3,220 lb.	3,700 lb.
Payload Capacity		4,910 lb.	4,640 lb.	4,260 lb.	3,780 lb.	6,290 lb.
Rear Door:	Style	Double Doors	Double Doors	Double Doors	Double Doors	Double Doors
	Width x Height	78" x 74"	78" x 74"	94" x 74"	94" x 74"	94" x 74"
	Hardware	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Side Door:	Width	36"	36"	36"	36"	36"
	Lock Style	Flush	Flush	Flush	Flush	Flush
Tube Main Rails:		2" x 4"	2" x 4"	2" x 6"	2" x 6"	2" x 6"
12V End Connector:		7-way	7-way	7-way	7-way	7-way
Stoneguard:		24"	24"	24"	24"	24"

*Also available in a 9,990 lb. GVWR

