

The Wells Fargo logo, consisting of the words "WELLS" and "CARGO" stacked vertically in a bold, white, sans-serif font, enclosed within a black circle. This circle is set against a yellow rectangular background in the top left corner of the page.

WELLS
CARGO®

IN PURSUIT OF ADVENTURE

When you see a trailer like this one, you understand what a motorcycle trailer should be — low and sleek and striking. It just commands attention. Beyond impressive styling, the Badlander motorcycle trailer appreciates the need to protect and pamper your ride: wheel chocks, floor/wall tie-downs, and Torflex® rubber torsion axles for a smooth journey. In many ways, the interior is as impressive as the exterior — black polybead flooring, white vinyl sidewall liner and ceiling liner. Built to last and designed to impress.



Trailers shown may feature optional equipment available at an additional charge.

BADLANDER

SPECIFICATIONS

BADLANDER

		BL712T2	BL714T2	BL716T2
Body:	Length	15'1"	17'1"	19'1"
	Width	7'0"	7'0"	7'0"
Overall:	Length	17'2"	19'2"	21'2"
	Width	8'6"	8'6"	8'6"
	Height	6'11"	6'11"	6'11"
Interior:	Length (including "V")	14'8"	16'8"	18'8"
	Width	6'9"	6'9"	6'9"
	Height	5'6"	5'6"	5'6"
Platform Height at Beavertail		13"	13"	13"
Torflex® Suspension E-Z® Lube Axles:		Tandem	Tandem	Tandem
Qty		7,000 lb.	7,000 lb.	7,000 lb.
Total Capacity		22.5° Up Angle	22.5° Up Angle	22.5° Up Angle
Type				
Electric Brakes with Breakaway Kit		Electric (both axles)	Electric (both axles)	Electric (both axles)
Radial Tire Size		ST205/75R15	ST205/75R15	ST205/75R15
Tire Load Range		C	C	C
Hitch Ball Size		2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball		13"	13"	13"
Hitch Weight (% of Curb Weight)		10% to 15%	10% to 15%	10% to 15%
GVWR		7,000 lb.	7,000 lb.	7,000 lb.
Curb Weight (Approximate)		2,600 lb.	2,800 lb.	3,000 lb.
Payload Capacity (Approximate)		4,400 lb.	4,200 lb.	4,000 lb.
Flush Lock Side Door Width - Width x Height		32" x 60"	32" x 60"	32" x 60"
Rear Ramp Door Opening - Width x Height		78" x 63"	78" x 63"	78" x 63"
Beavertail Length		24"	24"	24"
12v Male Connection		7-way	7-way	7-way

STANDARD FEATURES

- 3' V-Nose/Flat Roof Profile
- 16" OC Vertical Posts
- 16" OC Crossmembers
- 16" OC Roof Bows
- ArmorTech Coated A-Frame & Rear End Rail
- Rear Ramp Door with Ramp Extension & Ramp Door Transition
- Skid Pads
- 32" x 60" Side Entry Door
- E-Z Lube® Hubs
- 15" Radial Tires
- Black SpitFire Aluminum Wheels
- Polished Aluminum Rear Corners & Header
- Polished Aluminum Front Nose
- .030 Aluminum Exterior Bonded (smooth appearance)
- ATP Stoneguard
- Flow-Thru Sidewall Vents
- 12v LED Exterior Lighting
- Exclusive "Carbon Razor" Design Vinyl Graphics
- 6.5" Removable Chrome Wheel Chock(s)
- 5,000 lb. Floor D-Rings
- 1,000 lb. Wall Rope Rings
- 3/4" Textured Polybead Flooring & Ramp Deck
- 9mm White Vinyl Sidewall Liner
- White Vinyl Ceiling Liner with Black Coves & Spring Cover
- 12v LED Dome Lights with Wall Switch
- Rear ID Bar with Built-In Loading Light
- 3-Year Limited Warranty



Trailers shown may feature optional equipment available at additional cost.



www.wellscargo.com

Specifications, features, options, packages & pricing subject to change without notice. See your authorized Wells Cargo® dealer for more information.